At Siemens Healthineers, our purpose is to enable healthcare providers to increase value by empowering them on their journey towards expanding precision medicine, transforming care delivery, and improving patient experience, all enabled by digitalizing healthcare.

An estimated 5 million patients globally benefit every day from our innovative technologies and services in the areas of diagnostic and therapeutic imaging, laboratory diagnostics and molecular medicine, as well as digital health and enterprise services.

We are a leading medical technology company with over 170 years of experience and 18,000 patents globally. With more than 48,000 dedicated colleagues in 75 countries, we will continue to innovate and shape the future of healthcare.

ADVIA, Dimension, Dimension Vista, epoc, RAPIDLab, and all associated marks are trademarks of Siemens Healthcare Diagnostics Inc., or its affiliates. All other trademarks and brands are the property of their respective owners.

Product availability may vary from country to country and is subject to varying regulatory requirements. Please contact your local representative for availability.

Method comparison studies were performed at three sites.

Siemens Healthineers Headquarters

Siemens Healthcare GmbH Henkestr. 127 91052 Erlangen, Germany Phone: +49 913184-0 siemens-healthineers.com

Published by

Siemens Healthcare Diagnostics Inc.
Point of Care Diagnostics
2 Edgewater Drive
Norwood, MA 02062-4637
USA

Phone: +1 781-269-3000

epoc Blood Analysis System: Summary of Analytical Methods and Performance





epoc Blood Analysis System: Summary of Analytical Methods and Performance

Table of Contents	
Performance Data	
Glossary	
Methodologies	
pH	6
pCO ₂	3
pO ₂	10
TCO ₂	12
Sodium	14
Potassium	16
onized Calcium	18
Chloride	20
Hematocrit	22
Glucose	24
Lactate	26
BUN	28
Creatinine	30

Performance Data

The data summarized here are compiled from user performance verifications of the epoc® Blood Analysis System, performed as part of the implementation process.

Dr*ec*ision

The precision data provided for each analyte are the pooled averages of the precision data from performance verifications from 1–12 user sites.

Method comparison

Method comparison studies were performed by individuals who were thoroughly familiar with the operation, maintenance, and control of both the epoc system and comparative method systems before starting. Testing was performed at all sites using blood collected in either blood gas syringes or in green-top evacuated tubes.

Some samples were spiked with concentrated solutions to create samples with concentrations throughout the reportable range of each analyte. Each plot included in this summary is from 1–3 sites and is representative of the comparison of the epoc Blood Analysis System to each instrument.

Glossary

Accuracy is how close a result is to its true value.

Precision is reproducibility—how closely multiple results obtained from the same sample agree with each other.

n is the number of data points included in the data set.

x represents the comparison method in regression analysis.

y represents the test method in regression analysis.

Slope describes the angle of the line that provides the best fit of the test and comparison results. A perfect slope would be 1.00. Deviations from 1.00 are an indication of proportional systematic error.¹

Intercept (int't) or y-intercept describes where the line of best fit intersects the y-axis. The y-intercept should be an indication of constant systematic error.¹

 $\mathbf{S}_{y,x}$ describes the scatter of the data around the line of best fit. It provides an estimate of the random error between the methods and includes both the imprecision of the test and comparison methods, as well as possible matrix effects that vary from one sample to another. $\mathbf{S}_{y,x}$ will never be 0 because both methods have some imprecision.¹

r or **correlation coefficient** describes how closely the results between the two methods change together. The lower the r value, the more scatter there is in the data. The main use of r is to help assess the reliability of the regression data—r should never be used as an indicator of method acceptability.¹

Methodologies

pH is measured by potentiometry using a pH-selective membrane electrode. The concentration of hydrogen ions is obtained from the measured potential using the Nernst equation.

 pCO_2 is measured by potentiometry using a membrane-covered pH sensing electrode. The electrode voltage is proportional to the dissolved carbon dioxide concentration through the Nernst equation.

pO₂ is measured by amperometry using a membranecovered oxygen-sensing cathode electrode. The oxygen reduction current is proportional to the dissolved oxygen concentration.

 $\mathsf{TCO_2}$ is measured based on a modified Henderson-Hasselbalch equation, using pH and pCO_2 , and calibrated to match the International Federation of Clinical Chemistry (IFCC) Reference Measurement Procedure for Total Carbon Dioxide. Therefore, it is metrologically traceable to the IFCC $\mathsf{TCO_2}$ reference method. 2

Sodium is measured by potentiometry using an ion-selective membrane electrode. The concentration of sodium ions is obtained from the measured potential using the Nernst equation. The epoc sodium measurement is an undiluted (direct) method. Values may differ from those obtained by dilutional (indirect) methods.

Potassium is measured by potentiometry using an ion-selective membrane electrode. The concentration of potassium ions is obtained from the measured potential using the Nernst equation. The epoc potassium measurement is an undiluted (direct) method. Values may differ from those obtained by dilutional (indirect) methods.

Ionized calcium is measured by potentiometry using an ion-selective membrane electrode. The concentration of calcium ions is obtained from the measured potential using the Nernst equation.

Chloride is measured by potentiometry using an ion-selective membrane electrode. The concentration of chloride ions is obtained from the measured potential using the Nernst equation.

Hematocrit is measured by AC conductometry using two gold electrodes. The conductance of the blood sample in the fluidic path between the two electrodes, after correction for variable plasma conductivity through the measurement of sodium and potassium concentration, is inversely proportional to the hematocrit value.

Glucose is measured by amperometry. The sensor comprises an immobilized enzyme first layer coated onto a gold electrode of the electrode module, with a diffusion barrier second layer. The glucose oxidase enzyme is employed to convert glucose to hydrogen peroxide:

Glucose Oxidase

 β -D-glucose + O_2 + H_2O \longrightarrow D-gluconic acid + H_2O_2

and then uses an amperometric sensor to detect the enzymatically produced hydrogen peroxide. Peroxide detection is by redox-mediated (ABTS [2,2'-azino-bis 3-ethylbenzothiazoline-6-sulfonic acid] diammonium salt) horseradish peroxidase (HRP)-catalyzed reduction on a gold electrode.

$$H_2O_2 + HRP^{red} \longrightarrow HRP^{ox}$$
 $HRP^{ox} + Red \longrightarrow Ox + HRP^{red}$
 $Ox + e$ - \longrightarrow Red

The reduction current is proportional to the concentration of glucose in the test fluid. The epoc glucose result is reported as plasma-equivalent glucose concentration.

Lactate is measured by amperometry. The sensor comprises an immobilized enzyme first layer coated onto a gold electrode of the electrode module, with a diffusion barrier second layer. The lactate oxidase enzyme is employed to convert lactate to hydrogen peroxide:

> Lactate Oxidase

$$β$$
-D-lactate + O_2 + H_2O Pyruvic acid + H_2O_2

and then uses an amperometric sensor to detect the enzymatically produced hydrogen peroxide. Peroxide detection is by redox-mediated (ABTS [2,2'-azino-bis 3-ethylbenzothiazoline-6-sulfonic acid] diammonium salt) horseradish peroxidase (HRP)-catalyzed reduction on a gold electrode.

$$H_2O_2 + HRP^{red} \longrightarrow HRP^{ox}$$
 $HRP^{ox} + Red \longrightarrow Ox + HRP^{red}$
 $Ox + e- \longrightarrow Red$

The reduction current is proportional to the concentration of lactate in the test fluid.

BUN/Urea is measured by potentiometry using an ammonium ion selective electrode coated onto a gold electrode, covered with an enzymatic membrane second layer. The urease enzyme is employed to convert urea to ammonium ions:

Urea +
$$H_2O$$
 + $2H^+$ + Urease -> $2NH_4^+$ + CO_2

and then uses a potentiometric ion selective electrode to detect the enzymatically produced ammonium ion. The concentration of ammonium ions is obtained from the measured potential using the Nernst equation.

Creatinine is measured by amperometry. Each creatinine sensor is a three-layer enzyme electrode comprising a first immobilized enzyme creatinine-conversion underlayer coated onto a gold electrode, a second immobilized enzyme creatine screening layer, and a third diffusion barrier layer.

The creatinine electrode underlayer contains the enzymes creatinine amidohydrolase, creatine amidinohydrolase, and sarcosine oxidase, which convert creatinine to hydrogen peroxide in an enzyme product cascade:

Creatinine Amidohydrolase

Creatine + H_2O \longrightarrow Creatine Creatine

Creatine + H₂O → Sarcosine + Urea
Sarcosine
Oxidase

Amidinohydrolase

Sarcosine + O_2 + H_2O \longrightarrow Glycine + Formaldehyde + H_2O_2

and then uses the underlying gold electrode to detect the enzymatically produced hydrogen peroxide. Peroxide detection is by redox-mediated horseradish peroxidase (HRP)-catalyzed reduction.

$$H_2O_2 + HRP^{red} \longrightarrow HRP^{ox}$$
 $H_2O_2 + HRP^{ox} + Red \longrightarrow HRP^{red} + Ox$
 $Ox + e- \longrightarrow Red$

The reduction current is proportional to the concentration of creatinine in the test fluid.

Please refer to the epoc Blood Analysis System Manual for more information.

References:


- 1. Westgard JO. Basic method evaluation. 3rd ed. Madison, WI (USA): Westgard QC, Inc.; 2008 p. 77–78.
- A.H. Maas, P. Rispens, O. Siggaard-Andersen, W.G. Zijlistra, "On the reliability
 of Henderson-Hasselbalch equation in routine clinical acid-base chemistry",
 Ann. Clin. Biochem., 21, 26–39, 1984.
- IFCC 2001/3, "Reference Measurement Procedure for Substance Concentration Determination of Total Carbon Dioxide in Blood, Plasma or Serum," Clin Chem Lab Med, 39(3), 2001.

pH Method Comparison


рΗ

Precision Level 1	n	Mean	SD	%CV
	24	7.052	0.009	0.13%
Level 3	25	7646	0.007	0.09%


X: Abbott I-STAT System




pH
X: RAPIDLab® 1265 Blood Gas System by Siemens Healthineers
V: apper System




X: Radiometer ABL 700 System



X: IL GEM PREMIER 3000 System
Y: epoc System




PH
X: Nova Biomedical CRITICAL CARE XPRESS System



X_m (comparative)

рΗ

X: IRMA TRUPOINT System




pCO₂ Method Comparison

pCO₂ mmHg


Precision	n	Mean	SD	%CV
Level 1	24	67.2	2.30	3.41%
Lovol 3	25	20.8	0.68	3 25%



Y: epoc System




pCO₂
 X: RAPIDLab 1265 Blood Gas System by Siemens Healthineers
 Y: epoc System




pCO.

X: Radiometer ABL 700 System

Y: epoc System




pCO₂
X: IL GEM PREMIER 3000 System
Y: epoc System



pCO₂
X: Nova Biomedical CRITICAL CARE XPRESS System


Y: epoc System



pCO₂

X: IRMA TRUPOINT System


Y: epoc System





pO₂ Method Comparison


*p*O₂ mmHg


Precision	n	Mean	SD	%CV
Level 1	24	63.7	4.46	7.00%
Level 3	25	185 6	6 46	3 48%















TCO₂ Method Comparison


TCO₂ mmol/L

Precision	n	Mean	SD	%CV
Level 1	136	18.7	0.23	1.2%
Lovol 3	132	30.8	0.54	1 7%


TCO₂
X: Dimension® EXL Integrated Chemistry System by Siemens Healthineers
Y: one System




TCO₂
X: Dimension Vista® Intelligent Lab System by Siemens Healthineers
Y: epoc System




TCO,



X: Abbott ARCHITECT System
Y: epoc System



TCO₂
X: ROCHE COBAS
Y: epoc System



White Paper | epoc Blood Analysis System epoc Blood Analysis System | White Paper


Sodium Method Comparison

Sodium mmol/L


Precision	n	Mean	SD	%CV
Level 1	27	113	0.82	0.73%
Lovol 3	27	166	1.07	0.64%



X: Abbott I-STAT System




X: RAPIDLab 1265 Blood Gas System by Siemens Healthineers Y: epoc System




X: Nova Biomedical PHOX System





X: Ortho Clinical Laboratories VITROS System






Na⁺


X: Radiometer ABL 700 System

Y: epoc System




Na⁺

X: IL GEM PREMIER 3000 System Y: epoc System




Na⁺

X: Beckman Coulter



X: Dimension Integrated Chemistry System by Siemens Healthineers Y: epoc System




Potassium Method Comparison


Potassium mmol/L

Precision	n	Mean	SD	%CV
Level 1	27	2.1	0.043	2.04%
Level 3	27	6.3	0.075	1.20%







X: RAPIDLab 1265 Blood Gas System by Siemens Healthineers
Y: epoc System








X: Ortho Clinical Laboratories VITROS System




epoc Blood Analysis System | White Paper


X: Radiometer ABL 700 System



X: IL GEM PREMIER 3000 System
Y: epoc System




K*
X: Beckman Coulter



K+






Ionized Calcium Method Comparison

Ionized Calcium mmol/L


Precision	n	Mean	SD	%CV
Level 1	26	1.53	0.019	1.25%
Level 3	27	0.67	0.009	1 40%

Ca⁺⁺

X: Abbott I-STAT System




X: RAPIDLab 1265 Blood Gas System by Siemens Healthineers Y: epoc System




Ca**

X: Nova Biomedical PHOX System


Y: epoc System



Ca⁺⁺ X: Radiometer ABL 700 System



Ca⁺⁺
X: IL GEM PREMIER 3000 System
Y: epoc System



Chloride Method Comparison


Chloride mmol/L

Precision	n	Mean	SD	%CV
Level 1	20	76	0.53	0.69%
Level 3	20	125	0.94	0.76%

Chloride


X: Abbott I-STAT System





Chloride


X: ADVIA® Clinical Chemistry System by Siemens Healthineers Y: epoc System



Chloride

X: Radiometer ABL 800 System


Y: epoc System



Chloride


X: ROCHE COBAS 6000 System

Y: epoc System



Chloride

X: Beckman Coulter DXC System Y: epoc System




Hematocrit Method Comparison

Hematocrit %PCV


Precision	n	Mean	SD	%CV
Level 1	26	25	0.56	2.28%
Lovol 3	26	44	1 16	2 61%

X: Radiometer ABL 825 System






X: RAPIDLab 1265 Blood Gas System by Siemens Healthineers Y: epoc System




X: Nova Biomedical PHOX System

Y: epoc System




Hct

X: Sysmex XE System Y: epoc System




Hct


X: Abbott I-STAT System



Hct X: IL GEM PREMIER 3000 System




X: Beckman Coulter LH System Y: epoc System



Hct

X: Microcentrifugation (spun) Y: epoc System



Glucose Method Comparison


Glucose mg/dL

Precision	n	Mean	SD	%CV
Level 1	27	41.9	1.24	2.96%
Level 3	27	278	6.84	2 46%

Glucose


X: Abbott I-STAT System





Glucose


X: RAPIDLab 1265 Blood Gas System by Siemens Healthineers Y: epoc System



Glucose


X: Nova Biomedical CRITICAL CARE XPRESS System





Glucose


X: Ortho Clinical Laboratories VITROS System Y: epoc System



Glucose


X: Radiometer ABL 700 System

Y: epoc System



Glucose


X: IL GEM PREMIER 3000 System



Glucose


X: Beckman Coulter DXC System

Y: epoc System



Glucose

X: Dimension Integrated Chemistry System by Siemens Healthineers Y: epoc System



Lactate Method Comparison


Lactate mmol/L

Precision	n	Mean	SD	%CV
Level 1	27	0.97	0.045	4.67%
Lovol 3	28	5 96	0.225	3 77%

Lactate


X: Abbott I-STAT System

Y: epoc System




Lactate

X: RAPIDLab 1265 Blood Gas System by Siemens Healthineers Y: epoc System




Lactate

X: Ortho Clinical Laboratories VITROS System




Lactate

X: Roche MODULAR System Y: epoc System




Lactate

X: Radiometer ABL 700 System




Lactate

X: IL GEM PREMIER 4000 System Y: epoc System



Lactate

X: Dimension Integrated Chemistry System by Siemens Healthineers Y: epoc System




BUN Method Comparison

BUN mg/dL

Precision Level 1	n 137	Mean 49.9	SD 1.12	%CV 2.2%


BUN

 $\mathsf{X} : \mathsf{Dimension} \ \mathsf{Integrated} \ \mathsf{Chemistry} \ \mathsf{System} \ \mathsf{by} \ \mathsf{Siemens} \ \mathsf{Healthineers} \ \mathsf{Y} : \mathsf{epoc} \ \mathsf{System}$




BUN

X: Dimension Vista Intelligent Lab System by Siemens Healthineers Y: epoc System



BUN


X: ROCHE COBAS



BUN


X: Beckman DXC System

Y: epoc System



BUN

X: Abbott ARCHITECT System Y: epoc System



Notes


Creatinine Method Comparison

Creatinine mg/dL

Precision Level 1	n 20	Mean 0.91	SD 0.045	%CV 4.93%


Creatinine

X: ADVIA Clinical Chemistry System by Siemens Healthineers Y: epoc System




Creatinine

X: Abbott I-STAT System Y: epoc System



Creatinine

X: Beckman Coulter AU680 System Y: epoc System



Creatinine

X: ROCHE COBAS 6000 System Y: epoc System

