

Table of contents

\\USER

<table border="1"><tr><td>drbs 3T VA60</td></tr></table>	drbs 3T VA60
drbs 3T VA60	

<table border="1"><tr><td><table border="1"><tr><td>pelvis</td></tr></table></td></tr></table>	<table border="1"><tr><td>pelvis</td></tr></table>	pelvis
<table border="1"><tr><td>pelvis</td></tr></table>	pelvis	
pelvis		

<table border="1"><tr><td><table border="1"><tr><td>rectum Deep Resolve</td></tr></table></td></tr></table>	<table border="1"><tr><td>rectum Deep Resolve</td></tr></table>	rectum Deep Resolve
<table border="1"><tr><td>rectum Deep Resolve</td></tr></table>	rectum Deep Resolve	
rectum Deep Resolve		

<table border="1"><tr><td><table border="1"><tr><td><table border="1"><tr><td>localizer</td></tr><tr><td>t2_tse_tra</td></tr><tr><td>t2_tse_sag</td></tr><tr><td>t2_tse_sax</td></tr><tr><td>t2_tse_lax</td></tr><tr><td>ep2d_diff_sax</td></tr><tr><td>resolve_diff_sax</td></tr></table></td></tr></table></td></tr></table>	<table border="1"><tr><td><table border="1"><tr><td>localizer</td></tr><tr><td>t2_tse_tra</td></tr><tr><td>t2_tse_sag</td></tr><tr><td>t2_tse_sax</td></tr><tr><td>t2_tse_lax</td></tr><tr><td>ep2d_diff_sax</td></tr><tr><td>resolve_diff_sax</td></tr></table></td></tr></table>	<table border="1"><tr><td>localizer</td></tr><tr><td>t2_tse_tra</td></tr><tr><td>t2_tse_sag</td></tr><tr><td>t2_tse_sax</td></tr><tr><td>t2_tse_lax</td></tr><tr><td>ep2d_diff_sax</td></tr><tr><td>resolve_diff_sax</td></tr></table>	localizer	t2_tse_tra	t2_tse_sag	t2_tse_sax	t2_tse_lax	ep2d_diff_sax	resolve_diff_sax
<table border="1"><tr><td><table border="1"><tr><td>localizer</td></tr><tr><td>t2_tse_tra</td></tr><tr><td>t2_tse_sag</td></tr><tr><td>t2_tse_sax</td></tr><tr><td>t2_tse_lax</td></tr><tr><td>ep2d_diff_sax</td></tr><tr><td>resolve_diff_sax</td></tr></table></td></tr></table>	<table border="1"><tr><td>localizer</td></tr><tr><td>t2_tse_tra</td></tr><tr><td>t2_tse_sag</td></tr><tr><td>t2_tse_sax</td></tr><tr><td>t2_tse_lax</td></tr><tr><td>ep2d_diff_sax</td></tr><tr><td>resolve_diff_sax</td></tr></table>	localizer	t2_tse_tra	t2_tse_sag	t2_tse_sax	t2_tse_lax	ep2d_diff_sax	resolve_diff_sax	
<table border="1"><tr><td>localizer</td></tr><tr><td>t2_tse_tra</td></tr><tr><td>t2_tse_sag</td></tr><tr><td>t2_tse_sax</td></tr><tr><td>t2_tse_lax</td></tr><tr><td>ep2d_diff_sax</td></tr><tr><td>resolve_diff_sax</td></tr></table>	localizer	t2_tse_tra	t2_tse_sag	t2_tse_sax	t2_tse_lax	ep2d_diff_sax	resolve_diff_sax		
localizer									
t2_tse_tra									
t2_tse_sag									
t2_tse_sax									
t2_tse_lax									
ep2d_diff_sax									
resolve_diff_sax									

\\USER\drbs 3T VA60\pelvis\rectum Deep Resolve\localizer

TA: 13 sec Coil Selection: Auto Voxel Size: 1.7×1.7×7.0 mm³ Acc:: 2 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	Off
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	On
Auto Close Inline Display	On
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	On
Load Images to Graphic Segments	On
Graphic segment	All Segments
Inline Movie	Off

Routine

Slice Group	1
Slices	7
Distance Factor	120 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Slice Group	2
Slices	7
Distance Factor	120 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Slice Group	3
Slices	7
Distance Factor	120 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Phase Oversampling	20 %
FOV Read	400 mm
FOV Phase	100.0 %
Slice Thickness	7.0 mm
TR	700.0 ms
TE	89.00 ms
Averages	1
Concatenations	1
AutoAlign	---

Contrast - Common

TR	700.0 ms
TE	89.00 ms
MTC	Off
Magn. Preparation	None
Flip Angle Mode	Hyperecho
Flip Angle	100 deg

Contrast - Common

Fat-Water Contrast	Standard
Dark Blood	Off
Contrasts	1
Wrap-up Magn.	None
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	1
Multiple Series	Each Measurement

Resolution - Common

FOV Read	400 mm
FOV Phase	100.0 %
Slice Thickness	7.0 mm
Base Resolution	240
Phase Resolution	70 %
Interpolation	1.00

Resolution - Acceleration

Acceleration Mode	GRAPPA
Reference Scans	TSE/Separate
Acceleration Factor PE	2
Reference Lines PE	24
Deep Resolve	On
Phase Partial Fourier	5/8

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	2D
Normalize	Prescan
Image Filter	Off

Geometry - Common

Slice Group	1
Slices	7
Distance Factor	120 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Slice Group	2
Slices	7
Distance Factor	120 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Slice Group	3
Slices	7
Distance Factor	120 %

Geometry - Common

Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Phase Oversampling	20 %
FOV Read	400 mm
FOV Phase	100.0 %
Slice Thickness	7.0 mm
TR	700.0 ms
Multi-Slice Mode	Single Shot
Series	Ascending
Concatenations	1

Geometry - AutoAlign

Slice Group	1
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Slice Group	2
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
Slice Group	3
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	A >> P
AutoAlign	---
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm
H	0.0 mm
Initial Orientation	Transversal
Initial Rotation	0.00 deg

Geometry - Navigator**Geometry - Saturation**

Special Saturation	None
--------------------	------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H
Inline Composing	Off

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	H >> F
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Tune up
B1 Shim	TrueForm
CoilShim	Off
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
---------	----------

System - Tx/Rx

Frequency 1H	123.200000 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	1.000

Physio - Signal

1st Signal/Mode	None
TR	700.0 ms
Concatenations	1

Physio - Cardiac

Fat-Water Contrast	Standard
Magn. Preparation	None
Dark Blood	Off
FOV Read	400 mm
FOV Phase	100.0 %
Phase Resolution	70 %
Motion Correction	None

Physio - PACE

Resp. Control	Off
Concatenations	1

Inline - Subtraction

Subtract	Off
Measurements	1
StdDev	Off
Motion Correction	None
Save Original Images	On

Inline - MIP

MIP Sag	Off
---------	-----

Inline - MIP

MIP Cor	Off
MIP Tra	Off
MIP Time	Off
Radial MIP	Off
Save Original Images	On
MPR Sag	Off
MPR Cor	Off
MPR Tra	Off

Inline - Composing

Inline Composing	Off
------------------	-----

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	h
Dimension	2D
RF Pulse Type	Normal
Gradient Mode	Fast
Flow Compensation	None
Bandwidth	496 Hz/Px
Echo Spacing	5.22 ms
Turbo Factor	168

Sequence - Part 2

Introduction	On
Motion Correction	None

Sequence - Assistant

SAR Assistant	TR
Max. TR	1000.0 ms
Allowed Delay	0 s

\\USER\drbs 3T VA60\pelvisrectum Deep Resolve\2_tse_tra

TA: 1:12 min Coil Selection: Auto Voxel Size: 0.4x0.4x4.0 mm³ Acc:: 4 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	On
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	Off
Graphic segment	Default
Inline Movie	Off

Resolution - Common

FOV Read	400 mm
FOV Phase	100.0 %
Slice Thickness	4.0 mm
Base Resolution	528
Phase Resolution	100 %
Interpolation	On

Resolution - Acceleration

Acceleration Mode	GRAPPA
Reference Scans	Integrated
Acceleration Factor PE	4
Reference Lines PE	26
Deep Resolve	On
Phase Partial Fourier	Off

Routine

Slice Group	1
Slices	30
Distance Factor	20 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	40 %
FOV Read	400 mm
FOV Phase	100.0 %
Slice Thickness	4.0 mm
TR	5400.0 ms
TE	76.00 ms
Averages	1
Concatenations	1
AutoAlign	---

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	2D
Normalize	Prescan
Image Filter	Off

Geometry - Common

Slice Group	1
Slices	30
Distance Factor	20 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	40 %
FOV Read	400 mm
FOV Phase	100.0 %
Slice Thickness	4.0 mm
TR	5400.0 ms
Multi-Slice Mode	Interleaved
Series	Interleaved
Concatenations	1

Contrast - Common

TR	5400.0 ms
TE	76.00 ms
MTC	Off
Magn. Preparation	None
Flip Angle Mode	Constant
Flip Angle	160 deg
Fat-Water Contrast	Standard
Dark Blood	Off
Contrasts	1
Wrap-up Magn.	None
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	1
Multiple Series	Off

Geometry - AutoAlign

Slice Group	1
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
AutoAlign	---
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm
H	0.0 mm
Initial Orientation	Transversal
Initial Rotation	90.00 deg

Geometry - Navigator**Geometry - Saturation**

Special Saturation	Parallel F/H
Gap	11.00 mm
Thickness	50.00 mm

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H
Inline Composing	Off

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	H >> F
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Tune up
B1 Shim	TrueForm
CoilShim	Off
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
LR Balancing	Off

System - Tx/Rx

Frequency 1H	123.200000 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	1.000

Physio - Signal

1st Signal/Mode	None
-----------------	------

Physio - Signal

TR	5400.0 ms
Concatenations	1

Physio - Cardiac

Fat-Water Contrast	Standard
Magn. Preparation	None
Dark Blood	Off
FOV Read	400 mm
FOV Phase	100.0 %
Phase Resolution	100 %
Motion Correction	None

Physio - PACE

Resp. Control	Off
Concatenations	1

Inline - Subtraction

Subtract	Off
Measurements	1
StdDev	Off
Motion Correction	None
Save Original Images	On

Inline - MIP

MIP Sag	Off
MIP Cor	Off
MIP Tra	Off
MIP Time	Off
Radial MIP	Off
Save Original Images	On
MPR Sag	Off
MPR Cor	Off
MPR Tra	Off

Inline - Composing

Inline Composing	Off
------------------	-----

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	qtse
Dimension	2D
RF Pulse Type	Normal
Gradient Mode	Fast
Flow Compensation	None
Bandwidth	237 Hz/Px
Echo Spacing	9.44 ms
Free Echo Spacing	Off
Define	Turbo Factor
Turbo Factor	17
Echo Trains per Slice	12

Sequence - Part 2

Introduction	On
Phase Correction	Automatic
Compensate T2 Decay	Off
Fast Mode	Off
WARP	Off
Red. EC Sensitivity	Off
Acoustic noise reduction	On
Reduce Motion Sens.	On
Motion Correction	None

Sequence - Assistant

SAR Assistant	Flip Angle
Min Flip Angle	110 deg
Allowed Delay	30 s

\\USER\drbs 3T VA60\pelvis\rectum Deep Resolve_t2_tse_sag

TA: 4:26 min Coil Selection: Auto Voxel Size: 0.3×0.3×3.0 mm³ Acc:: 3 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	On
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	Off
Graphic segment	Default
Inline Movie	Off

Resolution - Common

FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
Base Resolution	368
Phase Resolution	100 %
Interpolation	On

Resolution - Acceleration

Acceleration Mode	GRAPPA
Reference Scans	Integrated
Acceleration Factor PE	3
Reference Lines PE	26
Deep Resolve	On
Phase Partial Fourier	Off

Routine

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Sagittal
Phase Encoding Dir.	F >> H
Phase Oversampling	150 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	5400.0 ms
TE	94.00 ms
Averages	4
Concatenations	1
AutoAlign	---

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	2D
Normalize	Prescan
Image Filter	Off

Geometry - Common

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Sagittal
Phase Encoding Dir.	F >> H
Phase Oversampling	150 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	5400.0 ms
Multi-Slice Mode	Interleaved
Series	Interleaved
Concatenations	1

Contrast - Common

TR	5400.0 ms
TE	94.00 ms
MTC	Off
Magn. Preparation	None
Flip Angle Mode	Constant
Flip Angle	160 deg
Fat-Water Contrast	Standard
Dark Blood	Off
Contrasts	1
Wrap-up Magn.	Restore
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	1
Multiple Series	Off

Geometry - AutoAlign

Slice Group	1
Position	Isocenter
Orientation	Sagittal
Phase Encoding Dir.	F >> H
AutoAlign	---
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm
H	0.0 mm
Initial Orientation	Sagittal
Initial Rotation	-90.00 deg

Geometry - Navigator**Geometry - Saturation**

Special Saturation	None
--------------------	------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H
Inline Composing	Off

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	H >> F
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Tune up
B1 Shim	TrueForm
CoilShim	Off
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
LR Balancing	Off

System - Tx/Rx

Frequency 1H	123.200000 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	1.000

Physio - Signal

1st Signal/Mode	None
TR	5400.0 ms
Concatenations	1

Physio - Cardiac

Fat-Water Contrast	Standard
Magn. Preparation	None
Dark Blood	Off
FOV Read	200 mm
FOV Phase	100.0 %
Phase Resolution	100 %
Motion Correction	None

Physio - PACE

Resp. Control	Off
Concatenations	1

Inline - Subtraction

Subtract	Off
Measurements	1
StdDev	Off
Motion Correction	None
Save Original Images	On

Inline - MIP

MIP Sag	Off
MIP Cor	Off
MIP Tra	Off
MIP Time	Off
Radial MIP	Off
Save Original Images	On
MPR Sag	Off
MPR Cor	Off
MPR Tra	Off

Inline - Composing

Inline Composing	Off
------------------	-----

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	tseR
Dimension	2D
RF Pulse Type	Normal
Gradient Mode	Fast
Flow Compensation	None
Bandwidth	295 Hz/Px
Echo Spacing	9.42 ms
Free Echo Spacing	Off
Define	Turbo Factor
Turbo Factor	27
Echo Trains per Slice	12

Sequence - Part 2

Introduction	On
Phase Correction	Automatic
Compensate T2 Decay	Off
Fast Mode	Off

Sequence - Part 2

WARP	Off
Red. EC Sensitivity	Off
Acoustic noise reduction	Off
Reduce Motion Sens.	On
Motion Correction	None

Sequence - Assistant

SAR Assistant	Flip Angle
Min Flip Angle	110 deg
Allowed Delay	30 s

\\USER\drbs 3T VA60\pelvis\rectum Deep Resolve_t2_tse_sax

TA: 4:26 min Coil Selection: Auto Voxel Size: 0.3×0.3×3.0 mm³ Acc:: 3 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	On
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	Off
Graphic segment	Default
Inline Movie	Off

Resolution - Common

FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
Base Resolution	368
Phase Resolution	100 %
Interpolation	On

Resolution - Acceleration

Acceleration Mode	GRAPPA
Reference Scans	Integrated
Acceleration Factor PE	3
Reference Lines PE	26
Deep Resolve	On
Phase Partial Fourier	Off

Routine

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	150 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	5400.0 ms
TE	94.00 ms
Averages	4
Concatenations	1
AutoAlign	---

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	2D
Normalize	Prescan
Image Filter	Off

Geometry - Common

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	150 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	5400.0 ms
Multi-Slice Mode	Interleaved
Series	Interleaved
Concatenations	1

Contrast - Common

TR	5400.0 ms
TE	94.00 ms
MTC	Off
Magn. Preparation	None
Flip Angle Mode	Constant
Flip Angle	160 deg
Fat-Water Contrast	Standard
Dark Blood	Off
Contrasts	1
Wrap-up Magn.	Restore
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	1
Multiple Series	Off

Geometry - AutoAlign

Slice Group	1
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
AutoAlign	---
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm
H	0.0 mm
Initial Orientation	Transversal
Initial Rotation	90.00 deg

Geometry - Navigator**Geometry - Saturation**

Special Saturation	None
--------------------	------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H
Inline Composing	Off

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	H >> F
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Tune up
B1 Shim	TrueForm
CoilShim	Off
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
LR Balancing	Off

System - Tx/Rx

Frequency 1H	123.200000 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	1.000

Physio - Signal

1st Signal/Mode	None
TR	5400.0 ms
Concatenations	1

Physio - Cardiac

Fat-Water Contrast	Standard
Magn. Preparation	None
Dark Blood	Off
FOV Read	200 mm
FOV Phase	100.0 %
Phase Resolution	100 %
Motion Correction	None

Physio - PACE

Resp. Control	Off
Concatenations	1

Inline - Subtraction

Subtract	Off
Measurements	1
StdDev	Off
Motion Correction	None
Save Original Images	On

Inline - MIP

MIP Sag	Off
MIP Cor	Off
MIP Tra	Off
MIP Time	Off
Radial MIP	Off
Save Original Images	On
MPR Sag	Off
MPR Cor	Off
MPR Tra	Off

Inline - Composing

Inline Composing	Off
------------------	-----

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	tseR
Dimension	2D
RF Pulse Type	Normal
Gradient Mode	Fast
Flow Compensation	None
Bandwidth	295 Hz/Px
Echo Spacing	9.42 ms
Free Echo Spacing	Off
Define	Turbo Factor
Turbo Factor	27
Echo Trains per Slice	12

Sequence - Part 2

Introduction	On
Phase Correction	Automatic
Compensate T2 Decay	Off
Fast Mode	Off

Sequence - Part 2

WARP	Off
Red. EC Sensitivity	Off
Acoustic noise reduction	Off
Reduce Motion Sens.	On
Motion Correction	None

Sequence - Assistant

SAR Assistant	Flip Angle
Min Flip Angle	110 deg
Allowed Delay	30 s

\\USER\drbs 3T VA60\pelvisrectum Deep Resolve\2_tse_lax

TA: 4:26 min Coil Selection: Auto Voxel Size: 0.3×0.3×3.0 mm³ Acc:: 3 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	On
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	Off
Graphic segment	Default
Inline Movie	Off

Resolution - Common

FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
Base Resolution	368
Phase Resolution	100 %
Interpolation	On

Resolution - Acceleration

Acceleration Mode	GRAPPA
Reference Scans	Integrated
Acceleration Factor PE	3
Reference Lines PE	26
Deep Resolve	On
Phase Partial Fourier	Off

Routine

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Coronal
Phase Encoding Dir.	R >> L
Phase Oversampling	150 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	5400.0 ms
TE	94.00 ms
Averages	4
Concatenations	1
AutoAlign	---

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	2D
Normalize	Prescan
Image Filter	Off

Geometry - Common

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Coronal
Phase Encoding Dir.	R >> L
Phase Oversampling	150 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	5400.0 ms
Multi-Slice Mode	Interleaved
Series	Interleaved
Concatenations	1

Contrast - Common

TR	5400.0 ms
TE	94.00 ms
MTC	Off
Magn. Preparation	None
Flip Angle Mode	Constant
Flip Angle	160 deg
Fat-Water Contrast	Standard
Dark Blood	Off
Contrasts	1
Wrap-up Magn.	Restore
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	1
Multiple Series	Off

Geometry - AutoAlign

Slice Group	1
Position	Isocenter
Orientation	Coronal
Phase Encoding Dir.	R >> L
AutoAlign	---
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm
H	0.0 mm
Initial Orientation	Coronal
Initial Rotation	0.00 deg

Geometry - Navigator**Geometry - Saturation**

Special Saturation	None
--------------------	------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H
Inline Composing	Off

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	H >> F
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Tune up
B1 Shim	TrueForm
CoilShim	Off
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
LR Balancing	Off

System - Tx/Rx

Frequency 1H	123.200000 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	1.000

Physio - Signal

1st Signal/Mode	None
TR	5400.0 ms
Concatenations	1

Physio - Cardiac

Fat-Water Contrast	Standard
Magn. Preparation	None
Dark Blood	Off
FOV Read	200 mm
FOV Phase	100.0 %
Phase Resolution	100 %
Motion Correction	None

Physio - PACE

Resp. Control	Off
Concatenations	1

Inline - Subtraction

Subtract	Off
Measurements	1
StdDev	Off
Motion Correction	None
Save Original Images	On

Inline - MIP

MIP Sag	Off
MIP Cor	Off
MIP Tra	Off
MIP Time	Off
Radial MIP	Off
Save Original Images	On
MPR Sag	Off
MPR Cor	Off
MPR Tra	Off

Inline - Composing

Inline Composing	Off
------------------	-----

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	tseR
Dimension	2D
RF Pulse Type	Normal
Gradient Mode	Fast
Flow Compensation	None
Bandwidth	295 Hz/Px
Echo Spacing	9.42 ms
Free Echo Spacing	Off
Define	Turbo Factor
Turbo Factor	27
Echo Trains per Slice	12

Sequence - Part 2

Introduction	On
Phase Correction	Automatic
Compensate T2 Decay	Off
Fast Mode	Off

Sequence - Part 2

WARP	Off
Red. EC Sensitivity	Off
Acoustic noise reduction	Off
Reduce Motion Sens.	On
Motion Correction	None

Sequence - Assistant

SAR Assistant	Flip Angle
Min Flip Angle	110 deg
Allowed Delay	30 s

\\USER\drbs 3T VA60\pelvis\rectum Deep Resolve\ep2d_diff_sax

TA: 2:35 min Coil Selection: Auto Voxel Size: 1.0×1.0×3.0 mm³ Acc:: 3 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	On
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	On
Load Images to Graphic Segments	Off
Graphic segment	3rd Segment
Inline Movie	Off

Routine

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	50 %
FOV Read	230 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	4300.0 ms
TE	63.00 ms
Concatenations	1
AutoAlign	---

Contrast - Common

TR	4300.0 ms
TE	63.00 ms
MTC	Off
Magn. Preparation	None
Fat-Water Contrast	Fat Saturation
Fat Saturation	Strong
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Delay in TR	0.00 ms

Resolution - Common

FOV Read	230 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
Base Resolution	110
Phase Resolution	100 %

Resolution - Common

Interpolation	On
---------------	----

Resolution - Acceleration

Acceleration Mode	GRAPPA
Reference Scans	EPI/Separate
Acceleration Factor PE	3
Reference Lines PE	30
Deep Resolve	On
Phase Partial Fourier	Off

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	2D
Static Field Correction	Off
Normalize	Off

Geometry - Common

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	50 %
FOV Read	230 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	4300.0 ms
Multi-Slice Mode	Interleaved
Series	Interleaved
Concatenations	1

Geometry - AutoAlign

Slice Group	1
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
AutoAlign	---
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm
H	0.0 mm
Initial Orientation	Transversal
Initial Rotation	90.00 deg

Geometry - Navigator**Geometry - Saturation**

Special Saturation	None
--------------------	------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H
Inline Composing	Off

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	H >> F
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Standard
B1 Shim	TrueForm
CoilShim	Off
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	90.00 deg
R >> L	230 mm
A >> P	230 mm
F >> H	66 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
Excitation	Standard

System - Tx/Rx

Frequency 1H	123.200000 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	3.000

Physio - Signal

1st Signal/Mode	None
TR	4300.0 ms
Concatenations	1

Physio - PACE

Resp. Control	Off
Concatenations	1

Diff

Diffusion Mode	3D Diagonal
Diff. Directions	1
Diffusion Scheme	Monopolar
Diff. Weightings	2
b-value 1	50 s/mm ²
b-value 2	1000 s/mm ²
Averages 1	3
Averages 2	28
Complex Averaging	On
Dynamic Field Correction	On
Invert Gray Scale	Off
Diff. Weighted Images	On
Trace Weighted Images	Off
Tensor	Off
FA Maps	Off
ADC Maps	On
Exponential ADC Maps	Off
b-value >=	0 s/mm ²
ADC Noise Threshold	20
Calculated Image	Off

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	epse
Excitation	Standard
RF Pulse Type	Normal
Gradient Mode	Fast
Bandwidth	1894 Hz/Px
Echo Spacing	0.63 ms
Free Echo Spacing	Off
Optimization	None
EPI Factor	110

Sequence - Part 2

Introduction	Off
Phase Correction	Internal
Ghost Reduction	Off

Sequence - Assistant

SAR Assistant	Off
Optimization	None

\\USER\drbs 3T VA60\pelvis\rectum Deep Resolve\resolve_diff_sax

TA: 3:36 min Coil Selection: Auto Voxel Size: 1.0×1.0×3.0 mm³ Acc:: 2 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	On
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	Off
Graphic segment	Default
Inline Movie	Off

Resolution - Common

FOV Phase	100.0 %
Slice Thickness	3.0 mm
Base Resolution	100
Phase Resolution	100 %
Interpolation	On

Resolution - Acceleration

Accel. Mode	GRAPPA
Reference Scans	EPI/Separate
Acceleration Factor PE	2
Reference Lines PE	50
Phase Partial Fourier	Off
Readout Partial Fourier	7/8
Readout Segments	5

Routine

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	0 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	4210.0 ms
TE 1	53 ms
TE 2	79 ms
Concatenations	1
AutoAlign	---

Resolution - Filter

Raw Filter	On
Distortion Correction	2D
Normalize	Off

Geometry - Common

Slice Group	1
Slices	20
Distance Factor	10 %
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
Phase Oversampling	0 %
FOV Read	200 mm
FOV Phase	100.0 %
Slice Thickness	3.0 mm
TR	4210.0 ms
Multi-Slice Mode	Interleaved
Series	Interleaved
Concatenations	1

Contrast - Common

TR	4210.0 ms
TE 1	53 ms
TE 2	79 ms
MTC	Off
Magn. Preparation	None
Flip Angle	180 deg
Fat-Water Contrast	Fat Saturation
Fat Saturation	Strong
Contrasts	2
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	1

Resolution - Common

FOV Read	200 mm
----------	--------

Geometry - AutoAlign

Slice Group	1
Position	Isocenter
Orientation	Transversal
Phase Encoding Dir.	R >> L
AutoAlign	---
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm
H	0.0 mm
Initial Orientation	Transversal
Initial Rotation	90.00 deg

Geometry - Saturation

Special Saturation	None
--------------------	------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H
Inline Composing	Off

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	H >> F
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Standard
B1 Shim	TrueForm
CoilShim	Off
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	IsoCenter
Orientation	Transversal
Rotation	90.00 deg
R >> L	200 mm
A >> P	200 mm
F >> H	66 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
---------	----------

System - Tx/Rx

Frequency 1H	123.200000 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	3.000

Physio - Signal

1st Signal/Mode	None
TR	4210.0 ms
Concatenations	1

Diff

Diffusion Mode	4-Scan Trace
----------------	--------------

Diff

Diff. Directions	4
Diffusion Scheme	Monopolar
Diff. Weightings	2
b-value 1	50 s/mm ²
b-value 2	1000 s/mm ²
Averages 1	1
Averages 2	2
Invert Gray Scale	Off
Diff. Weighted Images	Off
Trace Weighted Images	On
Tensor	Off
FA Maps	Off
ADC Maps	On
Exponential ADC Maps	Off
b-value >=	0 s/mm ²
ADC Noise Threshold	5
Calculated Image	Off

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	resolve
Dimension	2D
RF Pulse Type	Normal
Gradient Mode	Fast
Bandwidth	962 Hz/Px
Echo Spacing	0.38 ms
Optimization	Min. TE
EPI Factor	50

Sequence - Part 2

Introduction	On
Reacquisition Mode	Off

Sequence - Assistant

SAR Assistant	Off
Optimization	Min. TE